

Genio Pull Out Monobloc

Product code: AT2071 Product Finish: Chrome EAN13 barcode: 5060344155939



Product features:

- · Metal construction throughout
- Quarter turn handle action for precise flow control
- · Single spray pattern showerhead
- · Luscious European quality chromium plate finish
- · Supplied compete with flexible tail pipes for fast simple fitting


Additional information / Parts included:

SFC070240 fixing kit

The installation of this product should respect requirement IRN R090.

Note: the image shown may not reflect the product finish, chrome finish is typically depicted

Product dimensions:



- Overall Height / projection: 437 mm
- Exit reach: 230 mm • Exit height: 197 mm Centre distance(s):
- Base diameter(s): 45 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 55 mm
- Spout diameter: 20 mm Spout aerator size: M18f

Packaged properties:

Box length: 575mm Box depth: 80mm

Box width: 350mm Units per outer: 5

Tap only weight: 2.10kg Boxed weight: 2.70kg

Product flow characteristics:



- Min / Max water pressure: 1.00 / 5.50 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G Mixed flow rate at 3 bar (litres / min): 09.41
- Control valve type: M20 ceramic disc, quarter turn operation
- Product flow characteristics: Single flow
- Non return valve(s): Hot & cold (integral to tails), 1 x in spout head
- · Aerator type: Honeycomb aerator
- · Accepts revolve / spray areator: No
- · Spout connection method: Grub screw
- Tail pipe inlet / outlet size: M10 / 1/2" BSP Male
- Inlet pipe type / length: flexible stainless braided hose / 360 mm

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners,
- Regular cleaning will prevent the build-up of lime scale and dirt After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives
- Warranty Summary (Full details available on request) Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year