RS HNK C

RENAISSANC Tap Range Renaissance High Neck Pillar Taps Chrome



Features:

Long life and easy to use 1/4 turn ceramic disc valves

Product Certifications:

WRAS Certificate No: 2109904 WRAS Expiry Date: 30/09/2026

\$57.9 l/min


For more products, visit our website:


Metal handles

WRAS

Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Lever Handle			
Connection Inlet:	1/2" BSP			
Connection Outlet:	Anti-Splash			
Number of Tap Holes:	2			
Valve/Cartridge Type:	1/2" Ceramic Disc Valve - 1/4 turn			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	65°C			
Maximum Static Pressure (bar):	10 bar			
Isolation Included:	No			

Dimensions (measurements in mm)





	Flow Rates (l/min)							
但编编的	System Pressure (bar)	0.2	0.5	1	2	3	5	
	RS HNK C (Cold)	6.9	9.9	13.2	18.7	22.9	28.9	
	RS HNK C (Hot)	6.9	9.9	13.2	18.7	22.9	28.9	
TECHNICAL DATA SHEET	OT QUALITY VEARS VEARS ARANTER ARANTER ARANTER *		B	RIS	3T/		D5	

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com. * - 10 year guarantee applies to products purchased on or after 01/04/2021. Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.