OPUS Tap Range Opus Bath Filler Chrome





	\sim	tu	res:
Г	ea	ιu	res.

- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- 5 year parts and 1 year labour guarantee for peace of mind.
- Co-ordinating Bathroom taps, **Recess shower and Accessories** available.

Product Certifications:






For more products, visit our website: http://www.bristan.com




DATA

Specification			
Product Type:	Bathroom Taps		
Main Construction Material:	Brass		
Mount Type:	Deck		
Handle Type:	Paddle		
Connection Inlet:	3/4" BSP		
Connection Outlet:	M24 Flow Straightener		
Number of Tap Holes:	2		
Valve/Cartridge Type:	3/4" Ceramic Disc Valve - 1/4 turn		
Plumbing System Requirements:	Suitable for all plumbing systems		
Minimum Dynamic Pressure (bar):	0.2 bar		
Maximum Dynamic Pressure (bar):	5 bar		
Maximum Hot Water Temperature °C:	60°C		
Maximum Static Pressure (bar):	10 bar		
Flow Type:	Single		
Isolation Included:	No		







D6

115

Flow Rates (I/min) System Pressure (bar) 0.2 0.5 1 2 3 5 OPS BF C (mixed) 20.2 32 45 78 101 63 TECHNICAL

BR

Bris Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com

Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.