# EV KIT-EFB C

### SHOWER ACC Shower Range Economy Single Function Slide Bar Shower Kit

Chrome



#### Features:

- Single function, rub clean, anti-limescale handset
- Push button slider mechanism
- 1.5m hose
- Soap tray with integral closed loop hose retainer

#### **Product Certifications:**



WRAS Certificate No: 240503003 WRAS Expiry Date: 31/05/2029





For more products, visit our website: http <u>//www.bristan.com</u>



Specification					
Finish/Colour:	Chrome Plated				
Main Construction Material:	Brass				
Shower Kit:	Adjustable Riser				
Shower Head Type:	Single Function Handset				
Rub Clean Handset:	Yes				
Mounting Type:	Wall				
Plumbing System Suitability:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.2 bar				
Maximum Dynamic Pressure (bar):	5 bar				
Maximum Static Pressure (bar):	10 bar				
Maximum Hot Water Supply Temperature <sup>o</sup> C:	65				
Connection Inlet:	G 1/2"				
Connection Outlet:	G 1/2"				
Isolation Included:	No				
Check Valve Included:	No				
What's Included:	1 x Riser Rail, 1 x Plated Shelf, 1 x Handset, 1 x Hose Cone To Nut, 1 x Green Limiter, 4 x Screws, 4 x Rawl Plugs, 1 x Allen Key, 1 x Fitting Instructions				

#### Dimensions (measurements in mm)





Flow Rates (I/min)							
System Pressure (bar)	0.2	0.5	1	2	3	5	
Through Handset (mixed)	4.5	7.1	10	14.2	17.4	22.5	

## TECHNICAL DATA





Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com - Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.