FHC ABSQ01 C

SHOWER ACC Shower Range ABS 200mm Square Fixed Head Chrome



Specification							
Finish/Colour:	Chrome Plated						
Main Construction Material:	ABS Plastic						
Mounting Type:	Wall Mounted						
Minimum Dynamic Pressure (bar):	0.2 bar						
Maximum Dynamic Pressure (bar):	5 bar						
Maximum Static Pressure (bar):	10 bar						
Maximum Hot Water Supply Temperature °C:	60°C						
Connection Inlet:	1/2" BSP						
Isolation Included:	No						
What's Included:	1 x Shower Head, 1 x Fitting Instructions						

Dimensions (measurements in mm)

Features:

- Complete with swivel joint for angle adjustment
- Clam packed

Product Certifications:



WRAS Certificate No: 2304103 WRAS Expiry Date: 30/04/2028



♦ 20.1 l/min

For more products, visit our website: http://www.bristan.com



	200					
200						



Flow Rates (I/min)									
System Pressure (bar)	0.2	0.5	1	2	3	5			
Through Fixed Head (mixed)	5.2	8.2	11.6	16.4	20.1	25.9			

TECHNICAL DATA SHEET





Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.