

Warranty Information

Proof of purchase will be required.

The guarantee does not cover faults or damage caused by incorrect installation and/or maintenance, ordinary wear and tear, water composition, etc.

*Please see www.deva-uk.com for full terms and conditions of warranty

Cleaning

Your product has a high-quality finish and should be treated with care to preserve the visible surfaces. Never use abrasives or abrasive cleaning agents to clean this product clean regularly with contamination free warm water and a damp soft cloth. Do not use products containing chlorine bleach or hydrochloric acid as these can damage the product.

We have a policy of continuous improvement and reserve the right to change specifications without notice.

METHVEN UK LIMITED
METHVEN EXPERIENCE CENTRE
3/3A STONE CROSS COURT
YEW TREE WAY
GOLBORNE
WARRINGTON
WA3 3JD
UNITED KINGDOM

TEL: 0800 195 1602
FAX: 0844 406 8690
EMAIL: sales@uk.methven.com
www.methven.com

INST-One Hole Sink Mixer
02/09/2022

INST8-1

One Hole Sink Mixer

Installation Guide

Technical Specification

Operating Pressure

Min: 0.1 Bar

Max: 5.0 Bar

Operating Temperature

Hot: 65°C

Cold: 5°C

Inlet Connections

1/2" BSP

Features

- Suitable for a one hole sink
- Suitable for all water pressures
- Swivel Spout



Congratulations on your purchase of your new Deva by Methven One Hole Sink Mixer.

Our fitting instructions have been created with you in mind to provide you with all the information you require and, if you need any further help, please don't hesitate to contact our customer care team on 0800 195 1602.

Please read all of the instructions before installation.

General

Methven recommends this product is installed by a competent person in compliance with all relevant regional regulations.



Remove all packaging and check the components for damage before starting installation.

This product must not be modified in any way as this will invalidate the guarantee.

It is the responsibility of the installer to ensure a waterproof seal is achieved, after installation all connections must be checked for leaks.

All outlets used primarily for personal hygiene shall deliver water at a safe temperature as per regional regulations.

Do not stretch or twist hose



DO NOT crush
Hose or swaged
Ends

Installation Instructions

Before commencing installation, ensure that the system has been flushed to remove any debris which can damage the product.

- 1) Screw the threaded fixing bolt into the bottom of the mixer body
 - 2) Screw both Flexi Tails into the tap body, ensuring that the O-Ring on the tail is positioned inside the tap body. Hand tighten, do not use PTFE tape or similar to create the seal.
 - 3) Offer the tap up to the hole in the sink
 - 4) On the underside of the sink fit the rubber and metal horseshoe shaped washers onto the threaded fixing bolt and using the nut provided tighten until the tap is secure in the mounting hole.
- Note: Plastic Triangle - If required a under sink mounting triangle can be purchased, this should be used on thin work surfaces to help distribute the weight of the tap and provide a thicker mounting surface for the fixing kit to clamp to.
- 5) Connect the male end of the tail to the corresponding hot and cold inlets.
 - 6) Reinststate water supply and test for leaks.

Water Saving

Sink Mixers can be regulated.

If you require a flow regulator to be fitted to your product and the item you have purchased does not have this fitted, you will need to follow these instructions.



Remove the existing antispash using a spanner, then fit the new version ensuring to fit the rubber seal.

Fully tighten to create seal.

NOTE: Some sink mixers are divided flow and the antispash cannot be changed therefore hose seal regulators would be required.

The seal regulator replaces the rubber washer used in the flexi hose end. Place the regulator into the hose end with the black o-ring facing the water flow, so it is visible, before fitting the hose.

Note this regulator cannot be fitted to product with copper tails, but these can be changed to flexi-tails

