


Geberit Omega concealed cistern 12 cm, 6 / 3 litres, installation height 82 cm



Example image



Application purposes

- For drywall construction
- For installation in part-height prewall installations
- For floor-standing WCs

Characteristics

- Adjustable in depth
- Concealed cistern with top or front actuation
- Concealed cistern, fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- Immediate post flush possible with factory setting
- Welded flush bend
- Tool-free installation and maintenance work on concealed cistern
- Water supply connection on the left or rear left

Scope of delivery

- Water supply connection Rp 1/2" - R 1/2", compatible with MF, with integrated angle stop valve and hand wheel
- Protection box for service opening
- Flush bend extension, ø 45 mm
- Fastening for flush bend

- Protection cover box for service opening protects against moisture and dirt
- Protection box for service opening can be cut to length

Technical data

Flow pressure	0.1–10 bar
Operating temperature, water max.	25 °C
Flush volume, factory setting	5.8 / 3 l
Flush volume large, adjustment range	4 / 4.5 / 6 / 7.5 l
Flush volume small, adjustment range	2–4 l
Calculated flow rate	0.11 l/s
Minimum flow pressure for calculated flow rate	0.5 bar
Product material	Plastic

- Protection plug
- 2 fixing brackets
- Fastening material
- Geberit pull disc for Type 212 flush valve for Omega concealed cistern 82 cm

Art. no.	B	H	T
109.041.00.1	44 cm	39.5 cm	12 cm



- Flush valve features settings to enable either a 6 l and 3 l flush, 4.5 l and 3 l flush or a 4 l and 2.6 l flush. Note: must be used with pans designed for low volume flush.
- The cistern can be operated with used water (rainwater) provided it is passed through a filter system first