

Geberit Duofix frame for wall-hung WC, 112 cm, with Delta concealed cistern 12 cm, Delta20 flush plate







Application purposes

- · For drywall construction
- · For installation in part or room-height prewall installations
- For installation in room-height installation walls
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62 cm
- For floor constructions 0-20 cm

Characteristics

- Statically self-supporting frame, protected against corrosion with powder coating
- · Frame top open
- Frame with ø 9 mm drilling holes for fastening in wood frame construction
- Frame with holes to receive Geberit Duofix wall anchors for elements with frame top open
- Frame prepared for support brackets for WC ceramic appliances with small contact surfaces
- · Galvanized feet

- Feet adjustable 0-20 cm
- · Foot plates made of plastic
- Foot plate depth suitable for installation in U-profiles UW 50
- Connection bend can be mounted without tools
- · Concealed cistern with front actuation
- · Concealed cistern, fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- Immediate post flush possible with factory setting
- Water supply connection on the rear or top centre
- With conduit pipe for feed pipe for Geberit AquaClean shower toilets and for connection cable
- · Fastening option for electrical connection

Technical data

| Operating temperature, water max. | 25 ℃ |
|--------------------------------------|---------------|
| Flush volume, factory setting | 5.8/31 |
| Flush volume large, adjustment range | 4.5 / 6 / 7.5 |
| Flush volume small, adjustment range | 2–41 |

Scope of delivery

- Angle stop valve R 1/2", with adaptor ring
- Protection box for service opening, made of polystyrene foam
- 2 distance bolts
- · Geberit Delta20 flush plate for dual flush
- 2 wall anchors
- · Connection set for WC, ø 90 mm

- · Connection bend 90° made of PE-HD, ø 90 mm
- Adaptor socket made of PE-HD, ø 90 / 110 mm
- 2 protection plugs
- Crossbar for panelling support
- 2 threaded rods M12
- · Fastening material

| Art. no. | Colour / surface | В | Н | Т |
|--------------|---------------------|-------|--------|-------|
| 458.118.21.2 | gloss chrome-plated | 50 cm | 112 cm | 12 cm |

Accessories

· Geberit set of support brackets for WC ceramic appliances with small contact surfaces