
Geberit Monolith sanitary module for floor-standing WC, 114 cm, front cladding made of glass







Example image

Application purposes

- · For floor inlets
- · For renovations, conversions and new buildings
- For wall inlets with an inlet height of 18 cm
- For replacing floor-standing WCs with concealed cistern with maximum service opening height < 109 cm
- · For replacing low-level exposed cisterns
- For replacing half-high level exposed cisterns
- · For replacing floor-standing WCs with close-coupled exposed cistern
- For connecting Geberit AquaClean Tuma WC complete solution, floorstanding WC
- For connecting Geberit AquaClean WC enhancement solutions, with accessories
- · For replacing pressure flushing valves
- For mounting on finished floors
- · For installation in front of drywalls or solid walls

Characteristics

Dual flush

- Compensation of dimensional tolerances possible
- · Cistern, fully insulated against condensation
- · Side cladding made of aluminium brushed
- Self-supporting
- · Adjustable flush volume
- Water supply connection on the rear centre
- Water supply connection on the left/right possible with accessories
- · Water supply connection on the bottom

Technical data

Flow pressure	0.1–10 bar
Operating temperature, water max.	25 ℃
Flush volume, factory setting	6/31
Flush volume large, adjustment range	4.5 / 6
Flush volume small	31
Calculated flow rate	0.11 l/s
Minimum flow pressure for calculated flow rate	0.5 bar

Scope of delivery

- Water supply connection set with 2 angle stop valves, 1/2"
- Flush bend extension 160 mm
- Connection bend made of PP, ø 90 mm
- Sleeve made of EPDM, ø 44 / 55 mm

- Adaptor socket made of PE-HD, ø 90 / 110 mm
- · Fastening material
- · Base cover
- Fastening material for drywall

Art. no.	Colour / surface	В	Н	Т
131.033.SI.5	Front cladding: white glass Side cladding: aluminium	50.5 cm	114 cm	10.6 cm
131.033.JK.5	Front cladding: lava glass Side cladding: black chrome aluminium	50.5 cm	114 cm	10.6 cm
131.033.JL.5	Front cladding: sand grey glass Side cladding: aluminium	50.5 cm	114 cm	10.6 cm
131.033.SJ.6	Front cladding: black glass Side cladding: black chrome aluminium	50.5 cm	114 cm	10.6 cm

Accessories

- · Set of fixing bolts made of aluminium, for Geberit Monolith side cladding
- Conversion set for Geberit AguaClean WC enhancement solutions
- Lateral water supply connection set for Geberit Monolith sanitary module for WC



· Glass thickness 8 mm