

Geberit Duofix element for wall-hung WC, 98 cm, with Delta concealed cistern 12 cm







Application purposes

- · For drywall construction
- For installation in part-height prewall installations
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- · For wall-hung WCs with projection up to 62 cm
- For floor constructions 0-20 cm

Characteristics

- · Self-supporting frame, powder-coated
- · Frame top open
- Frame with ø 9 mm drilling holes for fastening in wood frame construction
- Frame prepared for support brackets for WC ceramic appliances with small contact surfaces
- · Galvanized feet
- Feet adjustable 0-20 cm
- · Foot plates made of plastic

- Foot plate depth suitable for installation in U-profiles UW 50
- · Connection bend can be mounted without tools
- · Concealed cistern with front actuation
- Concealed cistern, fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- Immediate post flush possible with factory setting
- Water supply connection on the rear or top centre
- With conduit pipe for feed pipe for connection of Geberit AquaClean shower toilets
- · Fastening option for electrical connection

Technical data

Maximum operating temperature, water	25 °C
Flush volume, factory setting	5.8 and 3 l
Flush volume large, adjustment range	4.5 / 6 / 7.5
Flush volume small, adjustment range	3-41

Scope of delivery

- Angle stop valve R 1/2", compatible with MF, with adapter ring
- Protection box for service opening, made of polystyrene foam
- · 2 distance bolts
- 2 wall anchors
- Connection set for WC, ø 90 mm

- Connection bend 90° made of PE-HD, ø 90 mm
- Adaptor socket made of PE-HD, ø 90 / 110 mm
- 2 protection plugs
- 2 threaded rods M12
- Fastening material

Art. no.	В	Н	T	
458.145.00.1	50 cm	98 cm	12 cm	New

Accessories

• Geberit set of support brackets for WC ceramic appliances with small contact surfaces