AQUACLASSIC 2 DUAL LEVER TAP ANTIQUE BRASS

TAC2AB/WH



Featuring a classic design with a tall sweeping neck spout, Aquaclassic 2 is available in a choice of several different coloured handle options.

The Aquaclassic 2 kitchen tap sits perfectly within a traditionally styled kitchen, the ideal accompaniment with a ceramic kitchen sink.

- This tap model features an antique brass finish with white handles
- Suitable for all pressure water systems
- Featuring an anti-splash spout with honeycomb aerator design which mixes air with water to emit a water flow with no splash

RANGEMASTER

SINKS & TAPS

Spout Reach (mm) 194 Spout Reach (mm) 229 Spout Rotation Range 360° Handle Type Dual Lever Colour Antique Brass Bar Pressure Suitability All Pressure Min. Bar Pressure 0.30 Max. Bar Pressure 5.50 Mixed Flow Rate at 3 Bar Pressure (l/min) Flow Type Dual Flow Recommended Hot Water Temperature 70°C Handle Control Quarter Turn Centre Distance (mm) - Cartridge Type Honeycomb Aerator Inlet Pipes Copper Rigid Tubes Anti-Splash Spout Yes Pull Out Spray No WRAS Approved No Product Code TAC2AB/WH		
Spout Height (mm) Spout Rotation Range 360° Handle Type Dual Lever Colour Antique Brass Bar Pressure Suitability Min. Bar Pressure 0.30 Max. Bar Pressure 5.50 Mixed Flow Rate at 3 Bar Pressure (l/min) Flow Type Dual Flow Recommended Hot Water Temperature Temperature Maximum Hot Water Temperature Centre Distance (mm) Cartridge Type Aerator Type Pull Out Spray WRAS Approved Anti-Splash Spout No	Overall Height (mm)	359
Spout Rotation Range 360° Handle Type Dual Lever Colour Antique Brass Bar Pressure Suitability All Pressure Min. Bar Pressure 0.30 Max. Bar Pressure 5.50 Mixed Flow Rate at 3 Bar Pressure (l/min) Flow Type Dual Flow Recommended Hot Water Temperature 70°C Maximum Hot Water Temperature 70°C Handle Control Quarter Turn Centre Distance (mm) Cartridge Type Ceramic Disc Cartridge Aerator Type Honeycomb Aerator Inlet Pipes Copper Rigid Tubes Anti-Splash Spout Yes Pull Out Spray No WRAS Approved	Spout Reach (mm)	194
Handle Type Colour Antique Brass Bar Pressure Suitability Min. Bar Pressure 0.30 Max. Bar Pressure 5.50 Mixed Flow Rate at 3 Bar Pressure (I/min) Flow Type Dual Flow Recommended Hot Water Temperature Temperature Maximum Hot Water Temperature Centre Distance (mm) Cartridge Type Aerator Type Inlet Pipes Anti-Splash Spout VRAS Approved All Pressure 1.8.13 18.13 18.13 Control Quarter Turn Ceramic Disc Cartridge Honeycomb Aerator Ves Pull Out Spray No	Spout Height (mm)	229
Colour Antique Brass Bar Pressure Suitability All Pressure 0.30 Max. Bar Pressure 5.50 Mixed Flow Rate at 3 Bar Pressure (I/min) Flow Type Dual Flow Recommended Hot Water Temperature Maximum Hot Water Temperature 70°C Handle Control Quarter Turn Centre Distance (mm) Cartridge Type Aerator Type Inlet Pipes Anti-Splash Spout Pull Out Spray WRAS Approved All Pressure All Pressure All Pressure 0.30 All Pressure 0.30 All Pressure 0.30 All Pressure 0.30 Each Cava 18.13 Pual Flow 46°C Ceramic Disc Cartridge Honeycomb Aerator Ves Pull Out Spray No	Spout Rotation Range	360°
Bar Pressure Suitability Min. Bar Pressure 0.30 Max. Bar Pressure 5.50 Mixed Flow Rate at 3 Bar Pressure (I/min) Flow Type Dual Flow Recommended Hot Water Temperature Maximum Hot Water Temperature 70°C Handle Control Centre Distance (mm) Cartridge Type Aerator Type Inlet Pipes Anti-Splash Spout Pull Out Spray WRAS Approved All Pressure 0.30 Anti-Splash Spout Pull Out Spray No	Handle Type	Dual Lever
Min. Bar Pressure Max. Bar Pressure 5.50 Mixed Flow Rate at 3 Bar Pressure (I/min) Flow Type Dual Flow Recommended Hot Water Temperature Maximum Hot Water Temperature 70°C Handle Control Quarter Turn Centre Distance (mm) - Cartridge Type Aerator Type Honeycomb Aerator Inlet Pipes Anti-Splash Spout Pull Out Spray No WRAS Approved No	Colour	Antique Brass
Max. Bar Pressure 5.50 Mixed Flow Rate at 3 Bar Pressure (I/min) 18.13 Flow Type Dual Flow 46°C Recommended Hot Water Temperature 70°C Maximum Hot Water Temperature Quarter Turn Centre Distance (mm) - Cartridge Type Ceramic Disc Cartridge Honeycomb Aerator Inlet Pipes Copper Rigid Tubes Anti-Splash Spout Yes Pull Out Spray No WRAS Approved No	Bar Pressure Suitability	All Pressure
Mixed Flow Rate at 3 Bar Pressure (I/min) Flow Type Dual Flow Recommended Hot Water 46°C Maximum Hot Water Temperature Handle Control Centre Distance (mm) Cartridge Type Aerator Type Inlet Pipes Anti-Splash Spout Pull Out Spray WRAS Approved Dual Flow Aeo C Cartridge Alerator Type Honeycomb Aerator Copper Rigid Tubes No	Min. Bar Pressure	0.30
Pressure (I/min) Flow Type Dual Flow Recommended Hot Water Temperature A6°C Maximum Hot Water Temperature Temperature Quarter Turn Centre Distance (mm) Cartridge Type Aerator Type Honeycomb Aerator Inlet Pipes Anti-Splash Spout Pull Out Spray WRAS Approved Dual Flow Ceramic Disc Cartridge Honeycomb Aerator Copper Rigid Tubes No	Max. Bar Pressure	5.50
Recommended Hot Water Temperature Maximum Hot Water Temperature 70°C Handle Control Quarter Turn Centre Distance (mm) Cartridge Type Aerator Type Honeycomb Aerator Inlet Pipes Anti-Splash Spout Pull Out Spray WRAS Approved 46°C 70°C Ceramic Disc Cartridge Honeycomb Aerator Copper Rigid Tubes Yes No		18.13
Temperature Maximum Hot Water Temperature 70°C Handle Control Quarter Turn Centre Distance (mm) - Cartridge Type Ceramic Disc Cartridge Honeycomb Aerator Inlet Pipes Anti-Splash Spout Yes Pull Out Spray WRAS Approved No	Flow Type	Dual Flow
Handle Control Quarter Turn Centre Distance (mm) - Cartridge Type Ceramic Disc Cartridge Honeycomb Aerator Inlet Pipes Copper Rigid Tubes Anti-Splash Spout Yes Pull Out Spray No WRAS Approved No		46°C
Centre Distance (mm) Cartridge Type Ceramic Disc Cartridge Aerator Type Honeycomb Aerator Inlet Pipes Copper Rigid Tubes Anti-Splash Spout Yes Pull Out Spray No WRAS Approved No	Maximum Hot Water Temperature	70°C
Cartridge Type Ceramic Disc Cartridge Honeycomb Aerator Inlet Pipes Copper Rigid Tubes Anti-Splash Spout Yes Pull Out Spray No WRAS Approved No	Handle Control	Quarter Turn
Aerator Type Honeycomb Aerator Inlet Pipes Copper Rigid Tubes Anti-Splash Spout Yes Pull Out Spray No WRAS Approved No	Centre Distance (mm)	-
Inlet Pipes Copper Rigid Tubes Anti-Splash Spout Yes Pull Out Spray No WRAS Approved No	Cartridge Type	Ceramic Disc Cartridge
Anti-Splash Spout Yes Pull Out Spray No WRAS Approved No	Aerator Type	Honeycomb Aerator
Pull Out Spray WRAS Approved No	Inlet Pipes	Copper Rigid Tubes
WRAS Approved No	Anti-Splash Spout	Yes
	Pull Out Spray	No
Product Code TAC2AB/WH	WRAS Approved	No
	Product Code	TAC2AB/WH
Barcode 5015834055749	Barcode	5015834055749

Date of download: July 02, 2024

AGA Rangemaster continuously seeks improvements in specification, design and production of products and thus, alterations take place periodically. Whilst every efforguide. Always refer to the installation instructions when fitting, installation work should be completed by a professional tradesman.	ort is made to produce up to date resources, the information included here is intended as a